




# VIRTUAL AIRSPACE MODELING AND SIMULATION PROJECT Technical Interchange Meeting III



Harry N. Swenson
Project Manager
NASA Ames Research Center

January 14-15, 2003





# **Goal and Objectives**



The Goal of the VAMS Project is to develop capabilities that lead to a significantly increase in the capacity of the National Airspace System, while maintaining safety and affordability.

#### The VAMS Objectives are:

- To define potential operational concepts.
- To generate supporting technology roadmaps.
- To establish the capability to assess these concepts.





#### **Deliverables / Products**




- Evaluated advance airspace system concept(s).
  - > Interim evaluations at domain and system level.
- Technology roadmap(s) to implement proposed concept(s).
  - > Annual updates of roadmaps at domain or system level.
- Validated modeling and simulation capability to assess new operational concepts at the domain and system-wide level.
  - > Annual builds of non-real-time modeling and simulation capability.
  - > Annual updates of real-time simulation capability.





# **Approach**








# **Operational Concepts Identified**








Metron - Surface Traffic Automation
Optimal Synthesis - Surface Operation Automation



# Modeling and Simulation Description









## Non-Real-Time System-Level Modeling and Simulation System Accomplishments



- April 2002: Demonstrated a proof-of-concept prototype.
  - -Selected the DoD's HLA-RTI infrastructure with agent-based software to enable fast-time NAS-wide simulation
  - -Established a modeling lab that leverages existing and emerging models and tools
- •February 2003: Proving the feasibility of the approach to capture the interactions between NAS entities.
  - -The baseline system, Build-1 provides:
    - Architectural foundation
      - -Creates an agent infrastructure
      - -Develops a robust HLA framework
    - Basic modeling toolbox
      - -Emulates the current NAS
      - -Simulates NAS-wide, gate-to-gate at low-resolution
      - -Models entire day-in-the-NAS scenario
      - -Some emphasis on modeling TFM interactions
    - ·Assessments
      - -Measure delay (gate, taxi, airborne)
      - -Fuel costs
      - -Controller workload (# of vectors, speed changes, # TFM restrictions, CD&R activity)
      - -TFM activity
  - -Five software tests have been completed; each verifies a key feature of the simulation system.









- August 2002: Conducted Preliminary Design Review (PDR.)
  - -Selected the DoD's HLA-RTI infrastructure with agent-based software
  - -Established a series of progressive Interim Tests to prove and deliver incremental operational simulation capabilities to the Project
- •November 2003: Interim Test #1provides the functionality approved in the PDR and establishes a firm baseline configuration for building the remainder of the VAST-RT simulation system,
  - -The baseline system, Build-1 provides:
    - Architectural foundation
      - -HLA based infrastructure
      - -Robust multi-simulator capability
    - Version 1 of the data communication toolbox
      - -Emulates the current legacy systems
      - -Provides enhanced communications capabilities
  - -Four test scenarios have been completed; each verifying a key feature of the simulation system.





#### **Scenario and Metric Framework**



# Stakeholder Viewpoints (questions to be answered)

Stakeholder Viewpoints (questions to be answered)

## operational scenarios

#### output metrics

## evaluation metrics

#### 1. Scope:

concepts

- •Issues
- NAS Domain
- Quantitative Goal

#### 2. Top Level Descriptions:

- Core ideas
- Assumptions

#### 3. Detailed Descriptions:

- Performance
- •Functions
- •Human Performance

#### 4. NAS infrastructure & Technology impacts:


- Transition planning
- Architecture
- Technology requirements

#### 5. NAS operational risks

- •Ensuring system integrity and redundancy
- Security
- Safety

#### 6. Key Project Attributes

- •Benefits/metrics
- Cost/metrics



#### **Scenario Elements:**


- •NAS Domain
- NAS Perturbations
- (e.g. Wx, Security Incidents)
- Origin/Destination Demand
- Assumed Technologies
- •Human/Machine Performance
- •Defined ATM Procedures
- •Assumed Equipage
- Fleet Mix
- •Traveling public



**Simulations** 

**NAS Model** 

#### **Empiric Analysis**



- •Number of communication events (requests,
- clearances, directives, etc.)
- •throughput (traffic volume)
- Delay
- •Safety incidents (proximity to minimum separation, incursions, encroachments, etc.)
- •Elapsed flight times
- •Fuel burn
- Capital investments
- Personnel workloads
- Noise
- Environmental impact

- •Average aircraft flight time per air route\*
- •Average aircraft payload per flight mile
- •Operational cost per passenger mile
- •Average taxi time from pushback to wheels up during peak traffic periods per specific airports or taxi paths within airports
- Average voice channel occupancy time per departure from pushback to take off
- Average Airport arrival rate during peak periods
- •Rate of arrivals per controller hour per airport
- •Aircraft (or engine, or other component) maintenance costs per flight mile
- Predictability
- \* a defined city pair air route






# **Evaluation and Assessment Accomplishments**



#### **Develop Methods & Requirements**



- Requirements to support validation of the real-time capabilities
  - Facility requirements
  - Data collection requirements
  - Software agent requirements
- Delivered 6/28/02











# **Evaluation and Assessment Accomplishments**



- Economic Forecast and Demand (GRA,LMI)
  - Scenario Planning

•GDP Growth (H/L), Airline Yields (H/L), Limits to Aviation System Growth (Many/Few), Substitutes to Commercial Air Travel (Good/Poor)

Five Scenarios pursued


- Non-Real Time Scenario and Metrics (VAMS Common Scenario Set)
  - Concept Analysis
  - •Storyboards
  - Data Sources
  - Dependent Variables
  - Scenario Element Breakdown
  - Dependent Variable Calculations





#### **VAMS Schedule**









# **Project Milestones**



1 2	"Identify candidate future ATS capacity-increasing operational concepts"  "Develop initial prototype VAST NRT airspace model toolbox w/system-level capabilities"	09/30/02 04/30/02
3A	"Complete definition of Initial Real-Time experimental requirements"	06/28/02
3	"Complete VAST RT environments definitions and preliminary design"	09/30/02
4	"Complete Build 1 VAST NRT state-of-the-art airspace models toolbox with the	
	ability to assess economic impact of new technology and NAS operational	
	performance and the ability to model the dynamic effects of interactive agents"	12/31/02
5	"Complete preliminary description of common scenario set & evaluation criteria	
	for operational concept assessment"	01/01/03
6	"Complete operational concept and roadmaps for introducing Wake vortex avoidance	
	into the Air Transportation System"	01/15/03
7	"Complete VAST Real-Time requirements and initial design"	06/30/03
8	"Complete self-evaluation of concepts and roadmaps"	02/13/04
9	"Complete definition of initial VAST Real-Time experiments"	04/30/04
10	"Complete preliminary evaluation of selected operational concepts (RT only)"	09/01/05
11	"Complete Build 3 VAST NRT toolbox with cognitive human performance	
	attributes and CNS models"	08/30/04
12	"Complete verification of initial VAST RT capabilities against an AATT derived	
	operational concept"	09/30/04
13	"Complete analysis and of capacity-increasing concepts and roadmaps w/VAST models,	
	simulations & Common Scenario Set"	12/15/04
14	"Complete verification of VAST Real-Time Multi-Facility capabilities"	06/30/05
15	"Complete Build 4 VAST NRT toolbox for advanced operational concept analysis"	09/30/05
16	"Complete definition and analysis of single system-level operational concept and	
	roadmap"	03/30/06
17		00/02/25
	Air Transportation System technology development"	06/30/06 13
		. •

